

Luméa Shell Mosaic Tile Specification

A decorative tile suitable for walls including wet areas

| | | | |
|---------------------|---|------------------------------|-------|
| Sizes | 25x25mm pieces | 10 sheets per m ² | 4.5kg |
| | 15x15mm pieces | 10 sheets per m ² | 3.5kg |
| Thickness | 2.3mm +/-0.2mm including web backing | | |
| Construction | Solid shell pieces glued on web backing. | | |
| Finish | Buff Polished. | | |
| Colours | Made from natural shell types: White mother of pearl, NZ abalone (Paua), Black Mother of pearl, Abalone pearl. | | |
| Cutting | Cut with a diamond blade tile wet saw or dry masonry blade. | | |
| Installation | Install with 2 pack epoxy adhesive and grouts ¹ . | | |
| | Because the shell is thinner than normal mosaic's care is needed to get the right volume of adhesive applied using a 1.5 – 2.0 mm notched trowel. Too much adhesive will show through on the finished surface. | | |
| Limitations | <ul style="list-style-type: none"> - Not suitable for places where intense heat may occur, such as fire surrounds, above oven hobs or on benches. - Use only non-abrasive cleaners. - As a natural product, shade, pattern and minor size variation are inherent characteristics. - Not suitable for salt or chlorine swimming pools. - Not suitable for permanent wet areas. - Not recommended below the shower line in of shower. | | |

These recommendations are a general guide only. For more specific details please contact us.

¹ e.g Litokol's 'Litoelastic' and 'Starlike' products or Mapei's 'Kerapoxy' and 'Ultracoulour Plus'